







Transducer-Class® Strain Gages

GAGE PATTERN	Actual size shown. Enlarged when necessary for definition	GAGE DESIGNATION See Note 1	RES. IN OHMS	STANDARD CREEP CODE	ENCAPSU- LATION OPTION AVAILABLE
	DIMENSIONS				

 				Often used on small column transducers.	
GAGE LENGTH	OVERALL LENGTH	GRID WIDTH	OVERALL WIDTH		
0.062	0.295	0.080	0.080		
1.57	7.49	2.03	2.03		
MATRIX SIZE	0.36 L x 0.14 W	9.0 L x 3.6 W		N2A-XX-S063Q-350	350 ± 0.2%
					Q*
					E2


 				General-purpose 90° tee rosette.	
GAGE LENGTH	OVERALL LENGTH	GRID WIDTH	OVERALL WIDTH		
0.062	0.133	0.075	0.168		
1.57	3.38	1.91	4.27		
MATRIX SIZE	0.24 L x 0.25 W	4.9 L x 5.8 W		N2A-XX-S064L-350	350 ± 0.2%
					L*
					E2


 				Encapsulated 90° tee rosette.	
GAGE LENGTH	OVERALL LENGTH	GRID WIDTH	OVERALL WIDTH		
0.080	0.170	0.110	0.240		
2.03	4.32	2.79	6.10		
MATRIX SIZE	0.23 L x 0.30 W	5.9 L x 7.6 W		J2A-XX-S114L-350 J2A-XX-S152M-10C	350 ± 0.4% 1000 ± 0.4%
					L M


*Only creep code available for this gage type.
Note 1: All products are RoHS compliant.

Transducer-Class® Strain Gages

GAGE PATTERN	Actual size shown. Enlarged when necessary for definition	GAGE DESIGNATION See Note 1	RES. IN OHMS	STANDARD CREEP CODE	ENCAPSU- LATION OPTION AVAILABLE
	DIMENSIONS				

				Designed for low-cost, half-bridge transducers. †BAL is balanced to ±0.2%, but RG is 350 ohms ±15%. ‡BAL is balanced to ±0.2%, but RG is 1000 ohms ±15%.				
GAGE LENGTH	OVERALL LENGTH	GRID WIDTH	OVERALL WIDTH					
GRID 1 0.060	0.180	GRID 1 0.120	0.175					
1.52	4.57	3.05	4.45					
MATRIX SIZE	0.22 L x 0.22 W		5.6 L x 5.6 W		N2A-XX-S153R-35B N2A-XX-S150R-1KB	BAL ± 0.2%† BAL ± 0.2%‡	R* R*w	E2 E2

				Often used on column transducers.				
GAGE LENGTH	OVERALL LENGTH	GRID WIDTH	OVERALL WIDTH					
0.100	0.415	0.130	0.130					
2.54	10.54	3.30	3.30					
MATRIX SIZE	0.48 L x 0.19 W		12.2 L x 4.8 W		N2K-XX-S165V-10C/DP	1000 ± 0.2%	V	E2


				Often used on column transducers.				
GAGE LENGTH	OVERALL LENGTH	GRID WIDTH	OVERALL WIDTH					
0.100	0.415	0.130	0.130					
2.54	10.54	3.30	3.30					
MATRIX SIZE	0.48 L x 0.19 W		12.2 L x 4.8 W		N2A-XX-S053P-350	350 ± 0.2%	P	E2


*Only creep code available for this gage type.


Note 1: All products are RoHS compliant.

Transducer-Class® Strain Gages

GAGE PATTERN	Actual size shown. Enlarged when necessary for definition	GAGE DESIGNATION See Note 1	RES. IN OHMS	STANDARD CREEP CODE	ENCAPSU- LATION OPTION AVAILABLE
	DIMENSIONS				

				General-purpose 90° tee rosette.				
GAGE LENGTH	OVERALL LENGTH	GRID WIDTH	OVERALL WIDTH					
0.125	0.230	0.150	0.340					
3.18	5.84	3.81	8.64	N2A-XX-S054Y-350	350 ± 0.2%	Y	E2	
				N2K-XX-S145R-10C/DP	1000 ± 0.2%	R	E2	
MATRIX SIZE	0.29 L x 0.40 W		7.4 L x 10.2 W		TK-XX-S145R-10C/DP	1000 ± 0.2%	R	E2

				Three-tab version of S145R pattern.				
GAGE LENGTH	OVERALL LENGTH	GRID WIDTH	OVERALL WIDTH					
0.125	0.230	0.150	0.340					
3.18	5.84	3.81	8.64					
MATRIX SIZE	0.29 L x 0.40 W		7.4 L x 10.2 W		N2K-XX-S146R-10C/DP	1000 ± 0.2%	R	E2
				TK-XX-S146R-10C/DP	1000 ± 0.2%	R	E2	

				Used on high-accuracy column load cells. (1) Gage length is 0.200 in (5.1 mm). (2) Transverse gage length is 0.050 in (1.27 mm).				
GAGE LENGTH	OVERALL LENGTH	GRID WIDTH	OVERALL WIDTH					
(1)	0.325	(2)	0.270	N2A-XX-S167R-350	350 ± 0.2%	R*	E2	
				N2K-XX-S015T-350/DP	350 ± 0.2%	T*	E2	
(1)	8.26	(2)	6.86	N2K-XX-S184T-10C/DP	1000 ± 0.2%	T*	E2	
				TK-XX-S015T-350/DP	350 ± 0.2%	T*	E2	
MATRIX SIZE	0.38 L x 0.33 W		9.6 L x 8.4 W		TK-XX-S184T-10C/DP	1000 ± 0.2%	T*	E2

*Only creep code available for this gage type.

Note 1: All products are RoHS compliant.

Disclaimer

ALL PRODUCTS, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE.

Vishay Precision Group, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "VPG"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

The product specifications do not expand or otherwise modify VPG's terms and conditions of purchase, including but not limited to, the warranty expressed therein.

VPG makes no warranty, representation or guarantee other than as set forth in the terms and conditions of purchase. **To the maximum extent permitted by applicable law, VPG disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.**

Information provided in datasheets and/or specifications may vary from actual results in different applications and performance may vary over time. Statements regarding the suitability of products for certain types of applications are based on VPG's knowledge of typical requirements that are often placed on VPG products. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. You should ensure you have the current version of the relevant information by contacting VPG prior to performing installation or use of the product, such as on our website at vpgsensors.com.

No license, express, implied, or otherwise, to any intellectual property rights is granted by this document, or by any conduct of VPG.

The products shown herein are not designed for use in life-saving or life-sustaining applications unless otherwise expressly indicated. Customers using or selling VPG products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify VPG for any damages arising or resulting from such use or sale. Please contact authorized VPG personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.

Copyright Vishay Precision Group, Inc., 2014. All rights reserved.