




Shear Patterns - Dual Grid

Transducer-Class® Strain Gages

GAGE PATTERN	Actual size shown. Enlarged when necessary for definition.	GAGE DESIGNATION See Note 1	RES. IN OHMS	STANDARD CREEP CODE	ENCAPSULATION OPTION AVAILABLE
	DIMENSIONS				

				Smaller version of T029/T030.			
GAGE LENGTH	OVERALL LENGTH	GRID WIDTH	OVERALL WIDTH				
0.075	0.220	0.060	0.170	N2A-XX-S203P-175	175 ± 0.2%	P	E3
1.91	5.59	1.52	4.32	N2A-XX-T031P-350	350 ± 0.2%	P	E3
				N2K-XX-T032P-350/DP	350 ± 0.2%	P	E3
				N2K-XX-S137Q-10C/DP	1000 ± 0.2%	Q	E3
				TK-XX-T032P-350/DP	350 ± 0.2%	P	
				TK-XX-S137Q-10C/DP	1000 ± 0.2%	Q	
MATRIX SIZE	0.28 L x 0.23 W		7.1 L x 5.8 W				


				Encapsulated version of T031/T032.			
GAGE LENGTH	OVERALL LENGTH	GRID WIDTH	OVERALL WIDTH				
0.075	0.22	0.060	0.190				
1.91	5.6	1.52	4.83	J2A-XX-S036R-350	350 ± 0.4%	R	
MATRIX SIZE	0.28 L x 0.25 W		7.1 L x 6.4 W		J5K-XX-S1448-350/DP	350 ± 0.4%	N/A


				Three-tab version of S036 pattern.			
GAGE LENGTH	OVERALL LENGTH	GRID WIDTH	OVERALL WIDTH				
0.075	0.216	0.060	0.190				
1.91	5.49	1.52	4.83				
MATRIX SIZE	0.28 L x 0.25 W		7.1 L x 6.4 W		J2A-XX-S254R-350	350 ± 0.4%	R


Note 1: All products are RoHS compliant.

Transducer-Class[®] Strain Gages

GAGE PATTERN	Actual size shown. Enlarged when necessary for definition.		GAGE DESIGNATION See Note 1	RES. IN OHMS	STANDARD CREEP CODE	ENCAPSULATION OPTION AVAILABLE
	DIMENSIONS	<div style="display: flex; align-items: center; gap: 5px;"> inch millimeter </div>				

				Rectangular-grid, 1000-ohm version of S036 pattern.		
GAGE LENGTH	OVERALL LENGTH	GRID WIDTH	OVERALL WIDTH	J2A-XX-S173R-10C	1000 ± 0.4%	R
0.085	0.226	0.114	0.200			
2.16	5.74	2.89	5.08			
MATRIX SIZE	0.28 L x 0.25 W		7.1 L x 6.4 W			

				Dual-element patterns for shear or torque transducers.			
GAGE LENGTH	OVERALL LENGTH	GRID WIDTH	OVERALL WIDTH	N2A-XX-T029Q-350 N2A-XX-S096H-10C N2K-XX-T030R-350/DP N2K-XX-S083R-10C/DP TK-XX-T030R-350/DP TK-XX-S083R-10C/DP	350 ± 0.2% 1000 ± 0.2% 350 ± 0.2% 1000 ± 0.2% 350 ± 0.2% 1000 ± 0.2%	Q H R R R R	E3 E3 E3 E3
0.125	0.318	0.10	0.250				
3.18	8.08	2.54	6.35				
MATRIX SIZE	0.38 L x 0.31 W		9.6 L x 7.9 W				


				Encapsulated versions of T029/S096.		
GAGE LENGTH	OVERALL LENGTH	GRID WIDTH	OVERALL WIDTH	J2A-XX-S101P-175 J2A-XX-S034P-350 J2A-XX-S122P-10C	175 ± 0.4% 350 ± 0.4% 1000 ± 0.4%	P P P
0.125	0.33	0.100	0.275			
3.18	8.4	2.54	6.99			
MATRIX SIZE	0.40 L x 0.34 W		10.1 L x 8.5 W			


Note 1: All products are RoHS compliant.

Shear Patterns - Dual Grid

Transducer-Class® Strain Gages

GAGE PATTERN	Actual size shown. Enlarged when necessary for definition.		GAGE DESIGNATION See Note 1	RES. IN OHMS	STANDARD CREEP CODE	ENCAPSULATION OPTION AVAILABLE
	DIMENSIONS	<input type="checkbox"/> inch <input checked="" type="checkbox"/> millimeter				

				Three-tab version of S034 pattern.		
GAGE LENGTH	OVERALL LENGTH	GRID WIDTH	OVERALL WIDTH	J2A-XX-S111K-350	350 ± 0.4%	K
0.125	0.33	0.100	0.275			
3.18	8.4	2.54	6.99			
MATRIX SIZE	0.40 L x 0.34 W		10.1 L x 8.5 W			

				Encapsulated dual-shear pattern with tabs at both ends of pattern.		
GAGE LENGTH	OVERALL LENGTH	GRID WIDTH	OVERALL WIDTH	J2A-XX-S245K-350	350 ± 0.4%	K
0.125	0.360	0.201	0.252			
3.18	9.14	5.10	6.40			
MATRIX SIZE	0.39 L x 0.29 W		9.9 L x 7.4 W			

Note 1: All products are RoHS compliant.



Disclaimer

ALL PRODUCTS, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE.

Vishay Precision Group, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "VPG"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

The product specifications do not expand or otherwise modify VPG's terms and conditions of purchase, including but not limited to, the warranty expressed therein.

VPG makes no warranty, representation or guarantee other than as set forth in the terms and conditions of purchase. **To the maximum extent permitted by applicable law, VPG disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.**

Information provided in datasheets and/or specifications may vary from actual results in different applications and performance may vary over time. Statements regarding the suitability of products for certain types of applications are based on VPG's knowledge of typical requirements that are often placed on VPG products. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. You should ensure you have the current version of the relevant information by contacting VPG prior to performing installation or use of the product, such as on our website at vpgsensors.com.

No license, express, implied, or otherwise, to any intellectual property rights is granted by this document, or by any conduct of VPG.

The products shown herein are not designed for use in life-saving or life-sustaining applications unless otherwise expressly indicated. Customers using or selling VPG products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify VPG for any damages arising or resulting from such use or sale. Please contact authorized VPG personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.

Copyright Vishay Precision Group, Inc., 2014. All rights reserved.